


APP Plastiflex Plastic Filler

Two-component Polyester filler that features with high elasticity. Purposed for works related to filling in case of dents and irregularities, as well as plastic components repairs.

Features with very good elasticity and perfect adhesion to any plastic components, including bumpers, spoilers, mirrors, trimmings and mudguards. Thanks to creamy consistency it offers easy modeling on complicated surfaces. Features with easy application and finish.



1765 g + 35 g

1,8 kg

Plastiflex

⁴⁸⁵ g

⁺15 g

0,5 kg

estiflex



IMPROVED BENDING **STRENGTH**

contains combination of dyes of resins.



EASY APPLICATION AND FINISHING

shortens significantly delivery of work related to application.



PERFECT ADHESION

For typical plastic, metal, wood and concrete.



PRODUCT IN BLACK-GRAPHITE COLOUR



















APP FLEX	APP PLASTIFLEX
Black-brown	Black-graphite
Good, liquid	Good, stable
Thin coats only. Limited filling properties.	Standard filling properties. Easy to apply, without running.
Standard drying time ca. 25-30 min.	Standard drying time ca. 25-30 min.
Standard	High elasticity
At the beginning may get stuck to sandpaper.	Very good finishing and high elasticity. Does not get stuck to sandpaper.
Possible irregularities in case of thick coat application.	Perfect filling. Good performance.

ADVANTAGES SHORT DRYING **VERY GOOD COLOUR (BLACK) SIMILAR TO** PLASTIC ORIGINAL COLOUR **ELASTICITY** TIME **VERY EASY GOOD ADHESION TO MOST** PERFECT FILLING FINISHING PLASTIC MATERIALS AND PERFORMANCE

APP No.	Product Description		Weight	Packing	Bulk Pack
010448	APP Plastiflex	Plastic Filler	0,5 kg	Can	18 items
010449	APP Plastiflex	Plastic Filler	1,8 kg	Can	8 items

