

• NTools SG 1002 / SG 828 Spray guns

Intended for spray application of:

- bases and primers,
- acrylic and polyurethane paint,
- colorless lacquers,
- water soluble and organic base lacquers.

The NTools SG 1002 and SG 828 spray guns due to their nozzle operation parameters and moderate compressed air requirement are intended for many functions in manufacturing and service applications.



Package content:

- gun body, set.,
- header tank, 600 ml,
- paint filter,
- key,
- brush,
- operating manual.

RELATED PRODUCT

APP ZOP 6

Header tank 600 ml

APP no. 639881



The compressed air hose connector (outer thread 1/4") is available with the spray gun.

1 NTools SG 1002

APP no. 161914, Ø 1,4 mm
APP no. 161917, Ø 1,7 mm

2 NTools SG 828

APP no. 161933, Ø 1,3 mm
APP no. 161934, Ø 1,4 mm

APP no. 161914, 161917, 161933, 161934

PRODUCT TECHNICAL PARAMETERS	
Type	HVLP
Paint transfer	> 65%
Nozzle diameter	1,3 / 1,4 / 1,7 mm
Nozzle and needle material	stainless steel
Max. operating pressure	10 bar
Operating pressure	3 bar
Air consumption	350 l/min
Recommended distance from the painted object	15-20 cm
Air connection	1/4"
Paint container connection	M 16x1,5 mm
Weight	476 g

APP no.	Product Name	Nozzle diameter	Unit pack.	
1	161914 NTools SG 1002	Spray gun	Ø 1,4 mm	1 pc.
	161917 NTools SG 1002	Spray gun	Ø 1,7 mm	1 pc.
2	161933 NTools SG 828	Spray gun	Ø 1,3 mm	1 pc.
	161934 NTools SG 828	Spray gun	Ø 1,4 mm	1 pc.